

TITLE OF THE INVENTION  
PRINT CONTROL METHOD AND APPARATUS

FIELD OF THE INVENTION

5           The present invention relates to a print control  
method, apparatus, and a computer program for  
controlling the apparatus and, more particularly, to a  
print control method and apparatus in a system  
including an information processing apparatus such as a  
10   personal computer or the like, and a printer.

BACKGROUND OF THE INVENTION

          Upon printing data such as text data, image data,  
or the like edited by an application program for  
15   editing text or image data, a print preview function  
that presents an image to be printed on the screen in a  
print layout to the user before the image is actually  
printed on a paper sheet is known. The print preview  
function is included in the application program, and  
20   has only a function of displaying a preview image.

          The user checks an image to be printed exploiting  
this print preview function, and can re-edit it by the  
application program until an ideal layout is realized.

          However, the print preview function provided by  
25   the application program cannot display, as a preview  
image, an image which reflects various print conditions

that a printer driver can set. Also, the user must set the size or the like of a preview image in accordance with the screen size, resulting in troublesome operation. For example, even when the user wants to  
5 simultaneously display preview images for several pages, the application program displays them with an arbitrary size and layout in response to a preview display instruction. For this reason, the user must re-set the size and layout after display. Even when the user  
10 re-sets them, a preview image is not always displayed according to that layout in which the image is to be printed.

#### SUMMARY OF THE INVENTION

15 The present invention has been made in consideration of the aforementioned prior art, and has as its object to provide a print control method and apparatus, which make preview display that reflects the print layout as faithfully as possible and is most easy  
20 to see without requiring the user to designate any layout for preview display, upon making print preview display.

More specifically, it is another object of the present invention to provide a print control method and  
25 apparatus, which display a preview image of a document including pages with various sizes and directions so

that a page with a maximum vertical size just fits in a  
preview display window, can efficiently use the display  
space, allow the user to preview the entire page by  
horizontally scrolling the display window, allow the  
5 user to visually understand relative page sizes in  
preview display by zooming other pages at the same  
ratio as the maximum page, and also allow the user to  
recognize not only the relative size but also the  
actual size by displaying the size of the designated  
10 page.

In order to achieve the above object, one aspect  
of the present invention has the following arrangement.

That is, a print control apparatus comprises:

search means for searching pages included in a  
15 print job for a page with a maximum size;

zoom means for zooming all pages included in the  
print job in a scale at which the page with the maximum  
size falls within a predetermined frame; and

display means for displaying preview images of  
20 all the zoomed pages.

Preferably, when a page is deleted from the  
stored print job, pages included in the print job are  
searched again for a page with a maximum size, and all  
pages included in the print job are displayed as  
25 preview images in a scale at which the page with the  
maximum size falls within the frame.

Preferably, the scale at which the page with the maximum size falls within the frame is a scale at which a vertical dimension of the page with the maximum size becomes smaller than a vertical dimension of the frame.

5            Preferably, when a page displayed within the frame is designated, a size of the designated page is displayed.

The apparatus preferably further comprises means for printing the stored print job.

10           The apparatus preferably further comprises storage means for storing print data in units of print jobs.

Other features and advantages of the present invention will be apparent from the following  
15 description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

#### 20            BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles  
25 of the invention.

Fig. 1 is a block diagram for explaining the arrangement of a print control apparatus according to an embodiment of the present invention;

Fig. 2 is a block diagram showing the arrangement  
5 of a typical print system built by a host computer to which a printer is connected;

Fig. 3 is a block diagram showing the arrangement of a print system which temporarily spools intermediate codes before a print command from an application is  
10 converted into a print control command;

Fig. 4 is a sectional view for explaining the printer in the present invention;

Fig. 5 is a flow chart showing the process in a spooler 302;

Fig. 6 is a flow chart showing print control in a  
15 spool file manager 304;

Fig. 7 is a flow chart showing the process in a despooler 305;

Fig. 8 shows an example of a print setup window;

Fig. 9 shows an example of a print spool setup  
20 window;

Fig. 10 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 11 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 12 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 13 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 14 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 15 is a flow chart showing a setup change process in a setup change editor 307;

Fig. 16 shows an example of a window that displays a list of print jobs spooled in the spool file manager 304;

Fig. 17 shows an example of a window of a previewer 306;

Fig. 18 shows an example of a window of the setup change editor 307;

Fig. 19 is a flow chart showing the process when data created by an application program or the like is printed with store designation;

Fig. 20 is a flow chart showing details of step S1903 in Fig. 19;

Fig. 21 is a flow chart showing the processing sequence upon operation of an edit button or combine button while a job is selected from a job list;

Fig. 22 is a flow chart showing the sequence for  
5 displaying a preview window upon operation of an edit button or combine button while a job is selected from a job list;

Fig. 23 is a flow chart showing details of step S2203 in Fig. 22;

10 Fig. 24 is a flow chart showing details of step S2204 in Fig. 22;

Fig. 25 is a flow chart showing details of step S2205 in Fig. 22;

Fig. 26 shows a display example of a job list;

15 Fig. 27 is a flow chart showing the sequence for rendering a page template;

Fig. 28 shows an example of preview display of pages having different sizes or directions; and

Fig. 29 shows an example of preview display when  
20 a page with a maximum size is deleted from the display shown in Fig. 28.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention  
25 will be described hereinafter.

<Arrangement of Printer Control System>

Fig. 1 is a block diagram for explaining the arrangement of a printer control system according to an embodiment of the present invention. Note that the present invention can be applied to any of a standalone  
5 device, a system built by a plurality of devices, and a system in which devices are connected via a network such as a LAN, WAN, or the like to execute processes, as long as the functions of the present invention are implemented.

10 Referring to Fig. 1, a host computer 3000 comprises a CPU 101 that processes a document including figures, images, text, tables (including a spreadsheet or the like), and the like on the basis of a document processing program stored in a program ROM in a ROM 3  
15 or an external memory 111, and systematically controls devices connected to a system bus 104. The program ROM in the ROM 103 or external memory 111 stores an operating system program (to be referred to as an OS hereinafter) or the like as a control program of the  
20 CPU 101, a font ROM in the ROM 103 or the external memory 111 stores font data or the like used in the document process, and a data ROM in the ROM 103 or the external memory 111 stores various data used upon  
25 executing the document process. A RAM 102 serves as a main memory, work area, and the like of the CPU 101.



A keyboard controller (KBC) 105 controls key input from a keyboard 109 and a pointing device (not shown). A CRT controller (CRTC) 106 controls display of a CRT display (CRT) 110. Reference numeral 107  
5 denotes a disk controller (DKC) which controls access to the external memory 111 such as a hard disk (HD), floppy disk (FD), and the like, which store a boot program, various application programs, font data, user files, edit files, a printer control command generation  
10 program (to be referred to as a printer driver hereinafter), and the like. A printer controller (PRTC) 108 is connected to a printer 1500 via a two-way interface (interface) 121 to implement a communication control process with the printer 1500.

15 Note that the CPU 101 rasterizes outline font data on a display information RAM assured on, e.g., the RAM 102 to realize WYSIWYG on the CRT 110. The CPU 101 opens various registered windows on the basis of commands instructed by a mouse cursor (not shown) or  
20 the like on the CRT 110, and executes various data processes. The user can set a print processing method for the printer driver including the printer setup and print mode selection by opening a window that pertains to the print setups upon executing a print process.

25 The printer 1500 is controlled by a CPU 112. The printer CPU 112 outputs an image signal as output

information to a print unit (printer engine) 117, which is connected to a system bus 115, on the basis of a control program or the like stored in a program ROM in a ROM 113, or a control program or the like stored in an external memory 114. The program ROM in the ROM 113 stores the control program and the like of the CPU 112. A font ROM in the ROM 113 stores font data or the like used upon generating the output information, and a data ROM in the ROM 113 stores information and the like used on the host computer when the printer has no external memory 114 such as a hard disk or the like.

The CPU 112 can communicate with the host computer via an input unit 118, and can inform the host computer 3000 of information or the like in the printer. A RAM 119 serves as a main memory, work area, and the like of the CPU 112, and its memory size can be expanded by an option RAM connected to an expansion port (not shown). Note that the RAM 119 is used as an output information rasterizing area, environment data storage area, NVRAM, and the like. Access to the aforementioned external memory 114 such as a hard disk (HD), IC card, or the like is controlled by a memory controller (DKC) 120. The external memory 114 is connected as an option, and stores font data, an emulation program, form data, and the like. Reference

numeral 1501 denotes a control panel on which operation switches, LED indicators, and the like are arranged.

The number of external memories 114 is not limited to one, but a plurality of external memories 114 may be connected. That is, a plurality of option font cards in addition to built-in fonts and external memories that store programs for interpreting printer control languages of different language systems may be connected. Furthermore, an NVRAM (not shown) may be connected, and may store printer mode setup information from the control panel 1501.

Fig. 2 shows the configuration of typical print processing software in the host computer to which a printing apparatus such as a printer or the like is connected directly or via a network. An application program (to be simply referred to as an application hereinafter) 201, graphic engine 202, printer driver 203, and system spooler 204 are program modules which are stored as files in the external memory 111, and are loaded onto the RAM 102 by the OS or a module that uses the corresponding module upon execution. The application 201 and printer driver 203 can be added to the files stored in the HD using the FD in the external memory 111 or a CD-ROM (not shown), or via a network (not shown). The application 201 stored in the external memory 111 is loaded onto the RAM 102 upon

execution. When the application 201 executes a print process with respect to the printer 1500, it outputs (renders) data using the graphic engine 202 which is similarly loaded onto the RAM 102 upon execution.

5           The graphic engine 202 loads a printer driver 203 which is prepared for each printing apparatus from the external memory 111 onto the RAM 102, and sets the output from the application 201 in the printer driver 203. The graphic engine 202 then converts a GDI  
10   (Graphic Device Interface) function received from the application 201 into a DDI (Device Driver Interface) function, and outputs the DDI function to the printer driver 203. The printer driver 203 converts the DDI  
15   function received from the graphic engine 202 into a control command, e.g., PDL (Page Description Language) that the printer can recognize. The converted printer control command is output as print data to the printer 1500 via the interface 121 by the system spooler 204 which is loaded onto the RAM 102 by the OS.

20           The print system of this embodiment also has an arrangement for temporarily spooling print data from the application as intermediate codes, as shown in Fig. 3, in addition to the print system constructed by the printer and host computer shown in Fig. 2.

25   <Print-related Software Modules in Embodiment>

Fig. 3 shows the expanded system of Fig. 2. This system temporarily generates a spool file 303 consisting of intermediate codes upon sending a print command from the graphic engine 202 to the printer driver 203. In the system shown in Fig. 2, the application 201 is released from the print process when the printer driver 203 has converted all print commands from the graphic engine 202 into printer control commands. By contrast, in the system shown in Fig. 3, a spooler 302 converts all print commands into intermediate code data, and the application 201 is released from the print process when it outputs print commands to the spool file 303. Normally, the latter system can shorten the processing time. In the system shown in Fig. 3, data as the contents of the spool file 303 can be processed. In this way, functions such as enlargement/reduction, reduced-scale print of a plurality of pages on one page, and the like that the application does not have can be implemented for print data from the application.

For these purposes, the system of this embodiment is attained by expanding the system shown in Fig. 2 to spool data as intermediate codes, as shown in Fig. 3. In order to process print data, setups are normally made from a window provided by the printer driver 203,

which saves the setup contents on the RAM 102 or external memory 111.

The arrangement in Fig. 3 will be explained in detail below. As shown in Fig. 3, in this expanded  
5 processing system, a dispatcher 301 receives a DDI function as a print command from the graphic engine 202. When the print command (DDI function) that the dispatcher 301 receives from the graphic engine 202 is based on a print command (GDI function) issued from the  
10 application 201 to the graphic engine 202, the dispatcher 301 loads the spooler 302 stored in the external memory 111 onto the RAM 102, and sends the print command (DDI function) to the spooler 302 in place of the printer driver 203.  
15 The spooler 302 interprets the received print command, converts it into intermediate codes in units of pages, and outputs the codes to the spool file 303. The spool file of intermediate codes stored in units of pages is called a page description file (PDF). Since  
20 one PDF corresponds to one print job, the spooled PDF is also often called a job or print job simply. The spooler 302 acquires processing setups (N-up, two-side, staple, color/monochrome designation, or the like) associated with print data set in the printer driver  
25 203 from the printer driver 203, and saves them as a setup file for each job in the spool file 303. The

setup file stored in units of jobs is called a job  
setup file (also called an SDF as an abbreviation for a  
spool description file). The job setup file will be  
described later. Note that the spool file 303 is  
5 generated as a file on the external memory 111, but may  
be generated on the RAM 102. Furthermore, the spooler  
302 loads a spool file manager 304 stored in the  
external memory 111 onto the RAM 102, and informs the  
spool file manager 304 of the generation state of the  
10 spool file 303. After that, the spool file manager 304  
checks if a print process can be done in accordance  
with the contents of the processing setups associated  
with print data, which are saved in the spool file 303.

If the spool file manager 304 determines that the  
15 print process can be done using the graphic engine 202,  
it loads a despooler 305 stored in the external memory  
111 onto the RAM 102, and instructs the despooler 305  
to execute the print process of the page description  
files of intermediate codes described in the spool file  
20 303.

The despooler 305 processes the page description  
files of intermediate codes included in the spool file  
303 in accordance with the job setup file which is  
included in the spool file 303 and includes processing  
25 setup information, re-generates a GDI function, and  
outputs it via the graphic engine 202 once again.

When the print command (DDI function) that the dispatcher 301 receives from the graphic engine 202 is based on a print command (GDI function) issued from the despooler 305 to the graphic engine 202, the dispatcher  
5 301 sends the print command to the printer driver 203 in place of the spooler 302.

The printer driver 203 generates a printer control command described in a page description language or the like on the basis of the DDI function  
10 acquired from the graphic engine 202, and outputs the generated command to the printer 1500 via the system spooler 204.

Furthermore, Fig. 3 shows an example which includes a previewer 306 and setup change editor 307 in  
15 addition to the expanded system described so far, and allows a print preview process, print setup change process, and combination process of a plurality of jobs.

In order to implement the print preview process, print setup change process, and combination process of  
20 a plurality of jobs, the user must designate "store" on a pull-down menu 901 as a means for "designating an output destination" in a property window of the printer driver shown in Fig. 9. When the user wants to only  
25 preview, he or she can select "preview" as designation of the output destination.



The contents set on the property window of the printer driver in this way are stored in a structure (for example, a structure called DEVMODE in Windows OS available from Microsoft Corp.) provided by the OS as a setup file. That structure includes, e.g., store designation. Store designation is a setup for storing a print command and processing setup in the spool file 303. When the spool file manager 304 reads the processing setup via the printer driver 203 and that setup includes store designation, the spool file 303 generates and stores a page description file and job setup file, as described above. Then, the window of the spool file manager 304 pops up, as shown in Fig. 16, and displays a list of jobs spooled by the spool file 303. Fig. 16 shows an example wherein four jobs are spooled, and operations for each job can be selected from a menu bar or by pressing menu icons below the menu bar. Operations that can be selected from the menu bar are the same as those of the menu icons. The following types of operations are available. Note that each operation is done while selecting a desired job. That is, there are 12 operations:

- (1) "print": executes a given job while selecting that job. That is, this operation prints the designated spool file.

- (2) "save & print": executes a print process while saving a job of the selected intermediate codes.
- (3) "preview": displays output preview in consideration of the print setups.
- 5       (4) "delete": deletes the selected job.
- (5) "copy": generates a copy of the selected job.
- (6) "combine": combines a plurality of jobs into one job.
- (7) "divide": divides the combined job into a  
10       plurality of original jobs.
- (8) "job edit" changes the print setups (layout setup, finishing setup, and the like) of an independent or combined job.
- (9) "move to top": moves the print order of a  
15       given job to the top of a job list.
- (10) "move up by one": advances the print order of a given job by one.
- (11) "move down by one": delays the print order of a given job by one.
- 20       (12) "move to last": moves the print order of a given job to the last of a job list.

When "preview" of an independent or combined job is designated on the window (Fig. 16) of the spool file manager, the previewer 306 stored in the external  
25       memory 111 is loaded onto the RAM 102, and is

instructed to execute a preview process of a job of the intermediate codes described in the spool file 303.

(Previewer)

The previewer 306 sequentially reads out page  
5 description files (PDF) of intermediate codes included  
in the spool file 303, processes them in accordance  
with the contents of processing setup information  
included in the job setup file (SDF) stored in the  
spool file 303, and outputs a GDI function to the  
10 graphic engine 202. The graphic engine 202 can output  
a preview window onto the screen by outputting  
rendering data on its own client area.

The graphic engine 202 can appropriately render  
in correspondence with the designated output  
15 destination. The previewer 306 implements preview by  
the method of processing intermediate codes included in  
the spool file 303 in accordance with the contents of  
the processing setups included in the spool file 303  
and outputting them using the graphic engine as in the  
20 despooler 305. In this way, since the processing  
setups set in the printer driver are stored as a job  
setup file in the spool file 303 and data of the page  
description file are processed and output based on the  
job setup file, a print preview approximate to an  
25 actual printout can be provided to the user in  
correspondence with the way actual rendering data is

printed, and designated processes (e.g., an N-up  
process (for laying out and printing N logical pages on  
one physical page), a two-sided print process, a  
bookbinding print process, a stamp process, and the  
5 like). Since the preview function of conventional  
application software such as document creation software  
renders based on page setups in that application, the  
print setups in the printer driver are not reflected in  
preview, and the user cannot recognize a preview of an  
10 image to be actually printed out.

One logical page is one page in data created by  
the application, and one physical page corresponds to  
one surface of one sheet (e.g., one paper sheet). More  
specifically, when the N-up process is designated,  
15 images for N pages created by the application are laid  
out and printed on a single sheet in a reduced scale.

By executing the preview process in this fashion,  
a large preview image of an image processed in  
accordance with the print processing setups saved in  
20 the spool file 303 is displayed on the screen by the  
previewer 306, as shown in Fig. 17. After that, the  
previewer 306 is closed in response to the user's  
non-display instruction (designation of "close)), and  
the control shifts to the window (Fig. 16) of the spool  
25 file manager.

When the user wants to print the contents displayed by the previewer 306, he or she issues a print request by selecting "print" or "save & print" on the spool file manager 304. In response to the print  
5 request, the despooler 305 generates a GDI function by processing each page description file based on the job setup file, and passes it to the graphic engine 202. Then, a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print  
10 process.

(Setup Change Editor)

A setup change process using the setup change editor 307 will be explained below.

The setup change process can be done for a  
15 "store"-designated job in Fig. 9 as in the preview process. The window of the spool file manager 304 pops up in the same sequence as in the preview process, and displays a list of spooled jobs. A setup change instruction is issued by designating "job edit" for the  
20 selected spool file on the window (Fig. 16) of the spool file manager. When the setup change instruction is issued, the setup change editor 307 stored in the external memory 111 is loaded onto the RAM and is instructed to display current or default processing  
25 setups. Then, a job setup window shown in Fig. 18 is displayed.

The setup change editor 307 acquires the job setup file of the "job edit"-designated job, and default values of the job setup window in Fig. 18 are changed on the basis of setup items designated in that job setup file. In the example shown in Fig. 18, the job setup file of the "job edit"-designated file is designated with the number of copies: 1, print method: one-sided, staple: none, layout: 1 page/sheet, and the like.

10 This setup change editor 307 can also make a small preview output on the window shown in Fig. 18 by processing each page description file of intermediate codes stored in the spool file 303 in accordance with the contents of the processing setups included in the job setup file stored in the spool file 303, and outputting them onto its own client area using the graphic engine.

Also, this editor can change and correct the contents of the processing setups included in the job setup file stored in the spool file 303. In this case, the user interface on the setup change editor 307 may have items that the printer driver 203 can set, or the user interface of the printer driver 203 itself may be called. As shown in Fig. 18, the number of copies, the print method (one-side, two-side, bookbinding print), staple (saddle finisher, or the like), page layout,

layout order, and the like can be designated. Upon pressing "detailed setups", most of items that the printer driver can designate can be re-set. However, changes of setups that pertain to print quality such as the resolution, graphic mode, and the like are not permitted.

When the changed items are confirmed in accordance with a confirmation request on the setup change editor 307, the control shifts to the spool file manager 304. The confirmed print setups that have been changed are saved. In this case, the setups are not saved in an original job setup file, but a new job output setup file used in the job edit process or the like is created to save the setups. Details of the job output setup file will be described later using Fig. 10 and the subsequent figures.

If the user wants to print in accordance with the changed setup contents as in the previewer 306, the spool file manager 304 issues a print request. The print request is sent to the graphic engine 202, and a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print process.

On the window (Fig. 16) of the spool file manager, the user can designate to combine a plurality of print jobs to execute them as a single print job. This process is also premised on the "store"-designated job

on the property window of the printer driver shown in Fig. 9 as in the preview and setup change processes.

When the user wants to combine print jobs, he or she calls the printer driver 203 from the application 5 201, and selects "store" from the user interface shown in Fig. 9. With this selection, the print job is stored in the spool file 303, and the window (Fig. 16) of the spool file manager pops up, as shown in Fig. 16. The spooled job is displayed as a list on the window of 10 the spool file manager. By repeating the same operation from the application 201, a plurality of jobs are spooled, and a list of jobs is displayed on the window of the spool file manager 304.

When the user selects a plurality of jobs from 15 the list and designates "combine", the setup change editor 307 stored in the external memory 111 is loaded onto the RAM 102 and is instructed to display the processing setups of the first job on the list or default setups. Then, a combine setup window shown in 20 Fig. 18 is displayed. In this embodiment, the same window as the setup change window is used as the combine setup window, but another window may be used.

The setup change editor 307 processes each page 25 description file of intermediate codes included in the spool file 303 in accordance with the contents of the processing setups included in job setup information



stored in the spool file 303, and outputs the processed data for all jobs designated as the combined job to its own client area using the graphic engine 202, thus outputting these jobs on the screen. In this case, 5 small preview images of all the selected jobs can be displayed on the preview region shown in Fig. 18. Upon generating the combined job, a job output setup file that expands the job setup files of the individual jobs is generated. This job output setup file is also 10 generated in the job edit process. That is, one job output setup file is generated for each job and also for the combined job.

In this case, images of the individual jobs may be displayed using the processing setups before they 15 are combined, or may be displayed by changing and correcting their setups to common processing setups of the combined job. In this case, the user interface on the setup change editor 307 may have items that the printer driver 203 can set, or the user interface of 20 the printer driver 203 itself may be called.

When the combined job and changed items are confirmed in accordance with a confirmation request on the setup change editor 307, as described above, the control shifts to the spool file manager 304. With 25 these operations, the plurality of jobs selected

previously are displayed as a single combined job on the window of the spool file manager.

When the user wants to print in accordance with the changed setup contents as in the previewer 306, the spool file manager 304 issues a print request. The print request is sent to the graphic engine 202, and a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print process.

#### <Arrangement of Laser Beam Printer>

Fig. 4 is a sectional view of a color laser printer having a two-sided print function as an example of the printer 1500.

This printer forms an electrostatic latent image by scanning the surface of a photosensitive drum 15 with a laser beam modulated by image data of each color obtained based on print data input from the host computer 3000 by a polygonal mirror 31. The electrostatic latent image is developed by toner to obtain a visible image, and visible images of all colors are transferred in turn onto an intermediate transfer drum 9 to form a color visible image. The color visible image is transferred onto a transfer medium 2, thus fixing the color visible image on the transfer medium 2. An image forming unit that makes the aforementioned control comprises a drum unit 13 having the photosensitive drum 15, a primary charger

having a contact charging roller 17, a cleaning unit, a developing unit, the intermediate transfer drum 9, a paper feed unit including a paper cassette 1 and various rollers 3 and 4, a transfer unit including a transfer roller 10, and a fixing unit 25.

The drum unit 13 integrates the photosensitive drum (photosensitive body) 15 and a cleaner container 14 which has a cleaning mechanism that also serves as a holder of the photosensitive drum 15. The drum unit 13 is detachably supported on a printer main body, and is easily exchanged as a unit in correspondence with the service life of the photosensitive drum 15. The photosensitive drum 15 is prepared by applying an organic photoconductor layer on the outer surface of an aluminum cylinder, and is rotatably supported by the cleaner container 14. The photosensitive drum 15 rotates upon receiving the driving force of a driving motor (not shown), and the driving motor rotates the photosensitive drum 15 counterclockwise in accordance with image forming operation. An electrostatic latent image is formed by selectively exposing the surface of the photosensitive drum 15. In a scanner unit 30, a modulated laser beam is reflected by the polygonal mirror which rotates by a motor 31a in synchronism with the horizontal sync signal of an image signal, and

strikes the photosensitive drum via a lens 32 and reflection mirror 33.

The developing unit comprises three color developers 20Y, 20M, and 20C for developing yellow (Y), magenta (M), and cyan (C) images, and a single black developer 21B for developing a black (B) image. The color developers 20Y, 20M, and 20C and the black developer 21B respectively have sleeves 20YS, 20MS, 20CS, and 21BS, and coating blades 20YB, 20MB, 20CB, and 21BB which are in press contact with the outer surfaces of these sleeves 20YS, 20MS, 20CS, and 21BS. Also, the three color developers 20Y, 20M, and 20C respectively have coating rollers 20YR, 20MR, and 20CR.

The black developer 21B is detachably attached to the printer main body, and the color developers 20Y, 20M, and 20C are detachably attached to a developing rotary 23 which rotates about a rotation shaft 22.

The sleeve 21BS of the black developer 21B is set to have a gap as small as, e.g., 300  $\mu\text{m}$  with respect to the photosensitive drum 15. In the black developer 21B, toner is fed by a feed member built in the developer, and is applied by the coating blade 21BB to the outer surface of the sleeve 21BS which rotates clockwise, thus charging the toner by triboelectrification. By applying a developing bias to the sleeve 21BS, the photosensitive drum 15 undergoes development in

accordance with an electrostatic latent image, thus forming a visible image on the photosensitive drum 15 by black toner.

The three color developers 20Y, 20M, and 20C rotate upon rotation of the developing rotary 23 in image formation, and a predetermined one of the sleeves 20YS, 20MS, and 20CS faces the photosensitive drum 15 to have a gap as small as 300  $\mu$ m. In this manner, a predetermined one of the color developers 20Y, 20M, and 20C stops at the developing position where it faces the photosensitive drum 15, thus forming a visible image on the photosensitive drum 15.

Upon forming a color image, the developing rotary 23 rotates once per rotation of the intermediate transfer drum 9 to execute developing processes in the order of the yellow developer 20Y, magenta developer 20M, cyan developer 20C, and black developer 21B. After four rotations of the intermediate transfer drum 9, visible images are formed in turn by yellow, magenta, cyan, and black toners, thus forming a full-color visible image on the intermediate transfer drum 9.

The intermediate transfer drum 9 contacts the photosensitive drum 15 and rotates upon rotation of the photosensitive drum 15. The drum 9 rotates clockwise upon forming a color image, and four visible images are transferred in turn onto the drum 9 from the

photosensitive drum 15. The transfer roller 10 (to be described later) contacts the intermediate transfer drum 9 upon forming an image, and clamps and conveys a transfer medium 2, thus simultaneously transferring a color visible image on the intermediate transfer roller 9 onto the transfer medium 2. A TOP sensor 9a and RS sensor 9b for detecting the position of the intermediate transfer drum 9 in its rotational direction, and a density sensor 9c for detecting the density of the toner image transferred onto the intermediate transfer drum are arranged around the intermediate transfer drum.

The transfer roller 10 comprises a transfer charger which is supported to be movable toward or away from the photosensitive drum 15, and is prepared by winding a middle-resistance foamed elastic member around a metal shaft.

The transfer roller 10 is located at its lower position, as indicated by the solid line in Fig. 4, so as not to disturb color visible images, while color visible images are transferred in turn onto the intermediate transfer drum 9. After the four color visible images are formed on the intermediate transfer drum 9, the transfer roller 10 moves to its upper position indicated by the dotted line in Fig. 1 by a cam member (not shown) in synchronism with the transfer

timing of the formed full-color visible image onto the transfer medium 2. In this manner, the transfer roller 10 is brought into press contact with the intermediate transfer drum 9 at a predetermined pressure via the transfer medium 2, and is applied with a bias voltage, thus transferring the full-color visible image on the intermediate transfer drum 9 onto the transfer medium 2.

The fixing unit 25 fixes the transferred full-color visible image while conveying the transfer medium 2, and comprises a fixing roller 26 for heating the transfer medium 2, and a pressing roller 27 for pressing the transfer medium 2 against the fixing roller 26. The fixing roller 26 and pressing roller 27 are formed into a hollow shape, and heaters 28 and 29 are respectively built therein. That is, the transfer medium 2 that holds the full-color visible image is conveyed by the fixing roller 26 and pressing roller 27, and the toner image is fixed on its surface by applied heat and pressure.

After the visible image is fixed, the transfer medium 2 is exhausted onto an exhaust unit 37 via exhaust rollers 34, 35, and 36, thus ending the image forming operation.

The cleaning means cleans any residual toner on the photosensitive drum 15 and intermediate transfer drum 9, and waste toner after the toner image formed on

the photosensitive drum 15 is transferred onto the intermediate transfer drum 9 or waste toner after the four color visible images formed on the intermediate transfer drum 9 are transferred onto the transfer medium 2 is stored in the cleaner container 14.

The transfer medium (recording sheet) 2 which is to undergo a print process is picked up from the paper tray or cassette 1 by the roller 3, and is conveyed while being clamped between the intermediate transfer roller 9 and transfer roller 10 to record a color toner image thereon. The toner image is fixed when the transfer medium 2 passes through the fixing unit 25. A guide 38 forms a convey path to guide the recording sheet toward the upper exhaust unit in a one-sided print process, but forms a path to guide it to a lower two-side unit in a two-sided print process.

The recording sheet guided to the two-side unit is temporarily fed to a portion (a convey path indicated by the two-dashed chain line) below the tray 1 by convey rollers 40, is then conveyed in the reverse direction, and is fed to a two-side tray 39. On the two-side tray 39, the paper sheet is upside down to that placed on the paper tray 1, and its convey direction is reversed. In this state, a toner image is transferred and fixed again, thus achieving the two-sided print process.



<Saving Process of Print Intermediate Data>

Fig. 5 is a flow chart showing the processing in the step of saving in units of pages upon generating the spool file 303 in the spooler 302.

5        In step 501, the spooler 302 receives a print request from the application via the graphic engine 202. The application displays a dialog that prompts the user to input print setups, as shown in Fig. 8, and the print setups input on this dialog are passed from the  
10       printer driver to the spooler 303. The setup input dialog shown in Fig. 8 includes a setup item 801 that determines the number of logical pages to be laid out per physical page, and the like.

      In step 502, the spooler 302 checks if the  
15       received print request is a job start request. If it is determined in step 502 that the received print request is a job start request, the flow advances to step 503, and the spooler 302 generates a spool file 303 for temporarily saving intermediate data.  
20       Subsequently, the spooler 302 informs the spool file manager 304 of the progress of the print process in step 504, and resets its page counter to 1 in step 505. The spool file manager 304 reads and stores information, processing setups, and the like of a job, the print  
25       process of which has started, from the spool file 303.

On the other hand, if it is determined in step 502 that the received print request is not a job start request, the flow advances to step 506.

The spooler checks in step 506 if the received  
5 request is a job end request. If it is determined that  
the received request is not a job end request, the flow  
advances to step 507 to check if the received request  
is a new page request. If it is determined in step 507  
that the received request is a new page request, the  
10 flow advances to step 508 to inform the spool file  
manager 304 of the progress of the print process. The  
spooler 302 then increments the page counter, closes a  
page description file that stores intermediate codes,  
and generates the next page description file.

15 If it is determined in step 507 that the received  
print request is not a new page request, the flow  
advances to step 509, and the spooler 302 prepares for  
export of intermediate codes to a page description file.

In step 510, the spooler 302 converts a DDI  
20 function of the print request into intermediate codes  
to store the print request in the spool file 303. In  
step 511, the spooler 302 writes the print request  
(intermediate codes) that has been converted into a  
storable format in a page description file of the spool  
25 file 303 in step 510. After that, the flow returns to  
step 501 to receive a print request from the

application again. The spooler 302 repeats a series of processes from steps 501 to 511 until it receives a job end request (EndDoc). The spooler 302 simultaneously acquires information such as processing setups and the  
5 like stored in the DEVMODE structure from the printer driver, and stores such information in the spool file 303 as a job setup file. On the other hand, if it is determined in step 506 that the print request from the application is a job end request, since the spooler 302  
10 has received all print requests from the application, the flow advances to step 512 to inform the spool file manager 304 of the progress of the print process, thus ending the processing.

#### <Generation of Spool File>

15 Fig. 6 is a flow chart showing details of control between the spool file 303 generation process and a print data generation process (to be described later) in the spool file manager 304.

In step 601, the spool file manager 304 receives  
20 a print process progress message from the spooler 302 or despooler 305.

The spool file manager 304 checks in step 602 if the progress message is a print start message which is sent from the spooler 302 in step 504 described above.  
25 If YES in step 602, the flow advances to step 603, and

the spool file manager 304 reads the print processing setups from the spool file 303 to start job management.

On the other hand, if it is determined in step 602 that the received progress message is not a print  
5 start message from the spooler 302, the flow advances to step 604, and the spool file manager 304 checks if the progress message is a print end message of one logical page which is sent from the spooler 302 in step 508 mentioned above. If the progress message is a  
10 print end message of one logical page, the flow advances to step 605 to store logical page information for that logical page.

It is then checked in step 606 if a print process of n logical pages that have been spooled at that time  
15 onto one physical page can start. If YES in step 606, the flow advances to step 607 to determine a physical page number on the basis of the number of logical pages assigned to one physical page to be printed.

As for a computation of a physical page, for  
20 example, when the processing setups lay out four logical pages on one physical page, the first physical page becomes ready for print when the fourth logical page has been spooled, thus determining the first physical page. Subsequently, the second physical page  
25 becomes ready for print when the eighth logical page has been spooled.

Also, even when the total number of logical pages is not a multiple of the number of logical pages to be laid out per physical page, logical pages to be laid out per physical page can be determined by a spool end message in step 512.

In step 608, the spool file manager 304 saves information such as the logical page numbers which form the physical page that is ready for print, the physical page number of that physical page, and the like in a job output setup file (a file including physical page information) in the format shown in Fig. 10, and informs the despooler 305 that physical page information for one physical page has been added. After that, the flow returns to step 601 to wait for the next message. In this embodiment, when print data for one page, i.e., logical pages that form one physical page have been spooled, a print process can start even when print jobs to be spooled still remain.

On the other hand, if it is determined in step 604 that the progress message is not a print end message of one logical page, the flow advances to step 609, and the spool file manager 304 checks if the progress message is a job end message sent from the spooler 302 in step 512 mentioned above. If YES in step 609, the flow advances to step 606 described above.

On the other hand, if the progress message is not a job end message, the flow advances to step 610, and the spool file manager 304 checks if the received message is a print end message of one physical page  
5 from the despooler 305. If the received message is a print end message of one physical page, the flow advances to step 611 to check if print processes for the processing setups are complete. If YES in step 611, the flow advances to step 612 to send a print end  
10 message to the despooler 305.

On the other hand, if it is determined that print processes for the processing setups are not complete yet, the flow advances to step 606 described above. The despooler 305 in this embodiment assumes one  
15 physical page as a unit for the print process. In step 608, information required for executing the print process of one physical page is saved in a file, so that such information can be used again. However, if such information need not be used again, a high-speed  
20 medium such as a shared memory or the like may be used to overwrite information in turn in units of physical pages, thus achieving both high processing speed and resource savings. On the other hand, when the progress of spooling is faster than that of despooling, or when  
25 despooling starts after completion of spooling of all pages, a message indicating that a plurality of

physical pages or all physical pages are ready for  
print is sent in accordance with the progress on the  
despooling side in place of sending a page print ready  
message for each physical page in step 608, thus

5 reducing the number of messages.

If it is determined in step 610 that the message  
is not a print end message of one physical page from  
the despooler, the flow advances to step 613, and the  
spool file manager 304 checks if the message is a print  
10 end message from the despooler 305. If it is  
determined that the message is a print end message from  
the despooler 305, the flow advances to step 614, and  
the spool file manager 304 deletes the corresponding  
page description files in the spool file 303, thus  
15 ending the processing. On the other hand, if the  
message is not a print end message from the despooler  
305, the flow advances to step 615 to execute another  
normal process and to then wait for the next message.

<Output of Spool File>

20 Fig. 7 is a flow chart showing details of the  
print data generation process in the despooler 305.

The despooler 305 reads out required information  
(page description file and job setup file) from the  
spool file 303 in response to the print request from  
25 the spool file manager 304, and generates print data.  
The method of transferring the generated print data to

the printer has already been explained with reference to Fig. 3.

Upon generating print data, the despooler 305 receives a message from the spool file manager 304 in  
5 step 701. The despooler 305 checks in step 702 if the input message is a job end message. If YES in step 702, the flow advances to step 703 to set an end flag, and the flow then jumps to step 705.

On the other hand, if it is determined in step  
10 702 that the received message is not a job end message, the flow advances to step 704 to check if the print start request of one physical page in step 608 mentioned above is received. If it is determined in step 704 that the received message is not a start  
15 request, the flow advances to step 710 to execute an error process, and the flow returns to step 701 to wait for the next message. On the other hand, if it is determined in step 704 that the received message is a print start request of one physical page, the flow  
20 advances to step 705, and the despooler 305 saves the IDs of physical pages, the print ready message of which was received in step 704.

The despooler 305 checks in step 706 if print  
processes of all pages of the physical page IDs saved  
25 in step 705 are complete. If YES in step 706, the flow advances to step 707 to check if the end flag was set



in step 703 mentioned above. If YES in step 707, the despooler 305 determines that the job print process is complete, and sends its processing end message to the spool file manager 304, thus ending the processing.

5           If it is determined in step 707 that the end flag is not set, the flow returns to step 701 to wait for the next message. If it is determined in step 706 that physical pages which are ready for print still remain, the flow advances to step 708. In step 708, the  
10   despooler 305 reads out unprocessed physical page IDs in turn from the saved physical page IDs, reads information required for generating print data of a physical page corresponding to each readout physical page ID, and executes a print process. The print  
15   process is done by converting by the despooler 305 a print request command stored in the spool file 303 into a format (GDI function) that the graphic engine 202 can recognize, and transferring it to the printer driver.

          As for the processing setups that lay out a  
20   plurality of logical pages on one physical page (to be referred to as an N-page print process hereinafter) as in this embodiment, conversion in this step is done in consideration of the layout upon reduction in scale. Upon completion of the required print process, the  
25   despooler 305 sends a print data generation end message of one physical page to the spool file manager 304 in

step 709. The flow returns to step 706 to repeat the  
aforementioned processes until print processes for all  
the physical page IDs of print ready pages, which were  
saved in step 705, are complete.

5           The flow of the print process using the  
dispatcher 301, spooler 302, spool file manager 304,  
and despooler 305 has been explained. With the above  
process, since the application 201 is released from the  
print process at the timing at which the spooler 302  
10 generates intermediate codes and stores them in the  
pool file 303, the application 201 can be released  
earlier than a case wherein a print command is directly  
output to the printer driver 203. Since intermediate  
files (page description file, job setup file) that  
15 consider the print setups of the printer driver are  
temporarily saved in the spool file 303, the user can  
recognize a print preview of an image to be actually  
printed, and can combine or sort print jobs generated  
by a plurality of applications. Also, the user can  
20 change print setups to execute a print process without  
launching the application again.

          In the print process using the spooler 302, a job  
output setup file is generated when the despooler 305  
issues a print request to the graphic engine, and is  
25 also generated when the preview process, job combine  
process, or the like is done. The job output setup

file is equivalent to a job setup file in case of an independent job, and is generated based on a plurality of pieces of job setup information in case of a combined job. The job output setup file will be explained below.

#### <Configuration of Job Output Setup File>

Fig. 10 shows an example of the job output setup file that saves information which is generated by the spool file manager 304 in step 608, and forms a print ready physical page. A field 1001 holds an ID that identifies a job, and may be held in the form of the name of a file or shared memory which saves this information. A field 1002 stores job setup information. The job setup information includes information unique to each job, such as a structure required for starting a job print process with respect to the graphic engine 202, designation of an N-page print process, designation of additional rendering of a page frame or the like, the number of copies, finishing designation such as staple, and the like. The job setup information in the field 1002 saves a required number of information in correspondence with the functions for a job. A field 1003 stores the number of physical pages of a job, and indicates the number of pieces of physical page information in correspondence with the value stored therein. Since this embodiment informs

the number of physical pages which are ready for print,  
this field may be omitted. Fields 1004 to 1007 store  
physical page information in correspondence with the  
value stored in the field 1003. The physical page  
5 information will be explained later using Fig. 12.

Fig. 11 shows an example of the job setup  
information in the field 1002 shown in Fig. 10. A  
field 1101 stores the total number of physical pages.  
A field 1102 stores the total number of logical pages.  
10 The fields 1101 and 1102 are used when the number of  
pages is printed as additional information in addition  
to print data. While a print process continues, these  
fields store tentative values, or the spool file  
manager 304 postpones generation of information of  
15 print ready physical pages until the print process ends.  
A field 1103 stores information indicating the number  
of copies to be printed of the print job of interest.  
A field 1104 stores information that designates if a  
print process is done in units of copy sets, when  
20 information set in the field 1103 indicates a print  
process of a plurality of sets of copies. A field 1105  
stores finishing information such as staple, punch,  
Z-fold, and the like, which information is designated  
when a finisher is available on the printer main body  
25 or an external device. A field 1106 stores additional  
print information, which saves information to be added

to a job such as decoration including a page frame or the like, additional information including a date or the like, the user name, the number of pages, watermark print, and the like. The number of fields included in  
5 this job setup information increases with increasing number of functions. For example, when a two-sided print function is available, a field for saving designation of two-sided print is added.

Fig. 12 shows an example of the physical page  
10 information in the field 1004 shown in Fig. 10. A first field 1201 stores a physical page number, which is a value used when the print order is managed or a physical page number is additionally printed. A field 1202 stores physical page setup information, which  
15 saves layout or color/monochrome setups when a layout or color/monochrome mode can be designated in units of physical pages. A field 1203 stores the number of logical pages assigned to the physical page of interest, and saves a value "4" or an ID indicating 4-page print  
20 when four pages are assigned per physical page.

A field 1204 and the subsequent fields save information of logical pages in correspondence with the number designated in the field 1203. Depending on the number of pages printed from the application 201, the  
25 actual number of page data sometimes becomes smaller than the number of pages designated by the field 1203.

In such case, logical page information saves special data indicating a blank page.

Fig. 13 shows an example of the physical page setup information in the field 1202. A field 1301 stores the layout order of logical pages on a physical page, and saves designation of the order that logical pages are laid out on a physical page (from upper left to right, from upper left to lower, and the like) in an N-page print process. In some systems, the field 1204 and the subsequent fields that store logical page information may be arranged not in a page number order but in the layout order in place of the setups in the field 1301.

A field 1302 stores information indicating the obverse or reverse surface of the two-sided print, which is used when, e.g., binding margins are to be formed on identical sides on the obverse and reverse surfaces. A field 1303 stores designation of a color or monochrome page, which is a value used when a printer has both monochrome and color modes, and color and monochrome pages of a document that includes both color and monochrome pages are to be printed in the color and monochrome modes, respectively. With this information, the color printer can change processes in units of pages as an auto color mode. That is, transfer control is done for a color page by completing

rotations of an intermediate transfer member  
(intermediate transfer drum or belt) or transfer member  
(transfer drum or belt) in correspondence with the  
number of device colors (four rotations in case of  
5 YMCK), and for a monochrome page by completing one  
rotation for black.

A field 1304 stores additional print information,  
which is used when additional information such as the  
number of pages, date, or the like is printed on a  
10 physical page. In the physical setup information, the  
number of fields increases in correspondence with the  
number of functions of the system.

Fig. 14 shows an example of logical page  
information stored in the field 1204. A field 1401  
15 stores the ID of a physical page. Using this ID, an  
intermediate code of a page description file  
corresponding to the logical page of interest is looked  
up from the spool file 303. This field may store a  
file or memory pointer, or an intermediate code itself  
20 that forms a logical page, as long as the intermediate  
code of a logical page can be accessed using this ID.

A field 1402 stores a logical page number, which  
is used when the logical page number is printed as  
additional information or as auxiliary information of  
25 the logical page ID. Format information in a field  
1403 saves various setup items that can be designated

in units of logical pages. For example, the format information saves additional print information such as a page frame and various kinds of setup information designated in units of logical pages such as an  
5 enlargement/reduction ratio and the like. Also, the format information can save attribute information of a logical page such as color/monochrome information in units of logical pages if necessary. Conversely, if a system need not switch setups in units of local pages  
10 or does not require any attribute information in units of logical pages, the field 1403 can be omitted.

The job output setup file has the aforementioned configuration. Note that the job setup file has nearly the same configuration. The job setup file saves a  
15 print method (one-sided, two-sided, bookbinding print), a print layout (N-up, poster print), additional information (addition of watermark, date, user name), the number of copies, and paper size information for each job. Also, the job setup file saves the layout  
20 order of logical pages, information indicating the obverse or reverse surface of two-sided print, color mode information, and the like in units of physical pages.

Furthermore, Fig. 3 shows the example in which  
25 the setup change editor 307 having a function of changing the setups of a job is added to the expanded



system described so far. In this embodiment, the setup contents of an independent job are contained in a job setup file, and those of a combined job are contained in a job output setup file shown in Fig. 10. In

5 addition, these files are independent from the page description file that saves intermediate codes. Hence, the setups of each job can be changed by editing the job output setup file. The setup change editor 307 edits or partially rewrites the job output setup file  
10 solely or in collaboration with the spool file manager 304, thus implementing the job setup change function.  
<Processing Sequence of Setup Change>

Fig. 15 is a flow chart showing details of the job setup change process in the setup change editor 307.

15 In step 1501, the setup change editor reads a job setup file or job output setup file. The job output setup file is the same file as that read by the previewer 306 and despooler 305.

The flow advances to step 1502 to display the  
20 read result to the user. In step S1503, the setup change editor interactively changes the setup contents by the aforementioned menu designation and the like with the user on the user interface shown in Fig. 18. This step may be attained in a batch manner that  
25 changes contents in accordance with setup change

contents written in a file or the like in place of the interactive manner.

The flow advances to step 1504, and the setup change editor compares the initially read contents and  
5 the currently designated setup contents to check if the contents have been changed. If the setup contents have been changed, the flow advances to step 1505 to generate a new job output setup file and inform the spool manager file of the changes, thus ending the  
10 processing. If it is determined in step 1504 that the setup changes are not changed, the setup change editor informs the spool file manager of that fact, thus ending the processing.

A new job output setup file is generated in this way. When an "OK" button 1801 is selected on the user  
15 interface window in Fig. 18, the new job output setup file is enabled, and the old job output setup file is deleted. When the job setup file of an independent job has been changed in place of the job output setup file,  
20 the old file is saved without being deleted. When a "restore defaults" button 1802 is selected on the window shown in Fig. 18, the new job output setup file is deleted, and the old job output setup file is enabled and reflected in display.

25 This embodiment has explained the setup change editor 307 as an independent module. Alternatively,

the setup change editor 307 may be a part of the user interface of the spool file manager 304. Also, the setup change editor 307 may be implemented as follows. That is, the editor 307 does not actually write change  
5 contents in the job output setup file and informs the spool file manager 304 of only the setup change contents, and the spool file manager 304 actually changes the job output setup file.

Fig. 3 shows the expanded system that combines a  
10 plurality of print jobs and prints them as a single print job. An expansion for despooling and previewing a combined job will be explained below.

Normally, spool files 303 with the intermediate format are generated in units of jobs. In case of an  
15 independent job, since a print process, setup change process, or the like is executed by sequentially reading out intermediate codes of respective logical pages in the job file to be processed, the logical page ID in the field 1401 can be implemented by a relative  
20 or absolute offset which indicates the location of each logical page in a file. In case of a combined job, a spool file and page information which belongs to that job must be specified from the job ID in the field 1401. In this embodiment, a spool file is specified by  
25 appending an ID that identifies a spool file to the logical page ID. In this case, only the field 1401 can

be modified. If the spool file can be identified, read of page information can be processed by the same logic as in the process of an independent job. In another implementation, when spool files are saved as

- 5 independent files in units of logical pages, the file name of each logical page may be used as the logical page ID in the field 1401.

#### <Preview Display in Store Process>

- The sequence for displaying a print preview image on the basis of a print job saved as intermediate data and a job output setup file will be explained below. When the user designates a store process of a print job from a menu 901, as shown in Fig. 9, in the print process from the application program, a print job
- 10 defined by intermediate codes and a job output setup file can be generated in the sequence shown in Fig. 5. As a result, a list of currently stored print jobs is displayed, as shown in Fig. 16. The user designates a desired print job from the print job list, and can edit
- 15 the print job, combine jobs, add the print job to the already combined print job, change the order of print jobs in the combined job, and so forth.
- 20

- In this case, when the user designates a given print job from the list and designates an operation
- 25 such as edit, combine, or the like from the button or menu, a print preview window of the entire designated

job is displayed, as shown in Fig. 18. Note that this print preview window can also display a preview image of the page relationship in the entire independent or combined print job unlike a normal preview window  
5 prepared by an application, which displays a preview image for each page.

Fig. 19 shows the sequence when data created by an application program or the like undergoes a print process while designating a store process. When the  
10 user selects "store" from the menu 901 as the output destination on the window shown in Fig. 9, and starts the print process, the sequence shown in Fig. 9 is executed.

In step S1901, the spooler is launched to  
15 generate and store intermediate data and a job output setup file. When "store" is designated, the spooler does not issue any print start instruction to the spool manager, and the intermediate data are held without being printed. The print job in this state is called a  
20 stored print job in this embodiment.

The print job that has been converted into and held as intermediate data in step S1901 is added to the already stored print job list in step S1902. In this embodiment, the stored print job is held only during  
25 execution of a program (the previewer 306 and setup change editor 307 in Fig. 3) for managing stored print

jobs, and is deleted upon quitting such program.  
However, the stored print job may be held until it is  
actually deleted.

When a new print job is added to the stored print  
5 job list, a list of these jobs is displayed in step  
S1903, as shown in Fig. 16. Note that a print job held  
as intermediate data is called a held job, and a job  
selected for the combine or edit process is called a  
target job.

10 <Display of Job List>

Fig. 20 is a flow chart showing details of step  
S1903 in Fig. 19. Note that the sequence in Fig. 20 is  
executed every time the state to be displayed has been  
changed, e.g., when a job is selected from the job list,  
15 thus updating the displayed job list.

It is checked in step S2001 if a plurality of  
jobs are selected. If NO in step S2001, it is checked  
in step S2002 if a job is selected. If YES in step  
S2002, that job is determined as a job of interest, and  
20 an edit button is enabled. The edit button is a button  
1608 in Fig. 16. Fig. 16 shows a state immediately  
after a single job is selected, and the edit button is  
enabled.

On the other hand, if no job is selected, a job  
25 which was selected in the previous process is  
determined as a job of interest in step S2004. If no

such job is available, i.e., if the job list is displayed for the first time, the first job in the job list is determined as a job of interest.

After the job of interest is determined, a job  
5 which cannot be combined with the job of interest is  
picked up from the held jobs, and the effect and reason  
why the job cannot be combined with the job of interest  
are written in a predetermined memory area or the like  
(step S2005). Note that at least one of setup item  
10 values, which cannot be changed after a job is  
generated (e.g., the designated resolution, the number  
of bits per pixel, graphic mode, or the like), of the  
job that cannot be combined with the job of interest is  
different from that of the job of interest.

15 Finally, the job list is displayed in step S2006.  
In this case, as for the job for which the effect and  
reason why it cannot be combined with the job of  
interest are set in step S2005, a symbol indicating  
that this job cannot be combined with the job of  
20 interest and a reason therefor are displayed in the  
column where that job is displayed. Fig. 26 shows this  
state. Since a job 2602 can be combined with a  
selected job 2601, but a job 2603 and subsequent jobs  
cannot be combined, symbols indicating that message are  
25 displayed on the left side of document names, and

reasons why these jobs cannot be combined are displayed in a comment field.

On the other hand, if a plurality of jobs are selected, it is checked in step S2007 if the selected  
5 jobs can be combined. If YES in step S2007, a combine button (a button 1606 in Fig. 16) is enabled (selectable) in step S2008, and the flow advances to step S2006 to display the job list.

If all the selected jobs cannot be combined, a  
10 message indicating that all the held jobs cannot be combined is set in step S2009. In step S2006, symbols and comments are displayed for the jobs for which the message indicating that they cannot be combined is set in step S2009.

15 In this way, the job list is displayed. As described above, since the sequence in Fig. 20 is executed every time a job is selected from the job list, jobs that can be combined with the selected job, and possibility of the edit or combine operation for the  
20 selected job can be presented to the user.

<Edit/combine Operation>

When the edit button (for a case wherein only one job is selected) or the combine button (for a case wherein a plurality of jobs are selected) is pressed  
25 while a job or jobs are selected from the display job list, the sequence shown in Fig. 21 is executed. When



jobs which cannot be combined are selected, no combine operation is available.

It is checked in step S2101 if the combine operation is made. If YES in step S2101, selected job  
5 output setup files are tentatively combined in step S2102. Since this operation is not settled, a tentative job output file is generated and used. Upon combining jobs, some setup values are changed to common values in place of the individual setups of the jobs.

10 As the method of setting common setups, the setup values may be changed to predetermined ones, or the setups of jobs other than the first job are set or cleared in correspondence with those of the first job. For example, the print methods of jobs to be combined  
15 are commonly set to be one-sided print unless they are all designated with two-sided print. Also, the setup values of the binding margin, staple designation, ascending/descending print order, face-up/down print, use of an inserter, and the like are set in  
20 correspondence with those of the first job. In addition, the setup values of the number of copies, bookbinding designation, and the like are cleared.

Preview display is executed using the job output setup file combined in step S2102 or that of a job  
25 selected as a job to be edited in step S2103, and a target job list is displayed in step S2104. The

preview window displays thumbnail images of all pages contained in jobs to be edited or combined in accordance with their layouts. On the other hand, the target job list displays the names, number of pages, and page layouts of jobs to be edited or combined. In this list display, in case of the combine operation, the job order can be sorted desirably, and a desired job can be deleted from the target jobs. When the target job is operated in this manner, the sequence shown in Fig. 21 is executed again, and the preview window and target job list are re-displayed.

Also, the print setups of the target job can be changed. Items that can be changed are those which can be changed by editing the job output setup file. Items that require operations of intermediate data are inhibited from being operated in this embodiment. However, all items may be re-set regardless of the processing time or resources required. Items that can be re-set in the system of this embodiment are the print method (one-sided/two-sided/bookbinding), the number of copies, the presence/absence of staple, and the like.

<Print Preview Display of Target Job>

Fig. 22 is a flow chart showing the sequence for displaying the job preview window shown in Fig. 18 when the user instructs desired operation such as job edit,

combine, or the like on the list display window of print jobs shown in Fig. 16, and shows details of step S2103 in Fig. 21.

Referring to Fig. 22, the layout setups of target jobs are acquired in step S2201. The layout setup items include the print method, page layout, page frame, finishing, paper feed switching, and the like, and these pieces of information are acquired from the job output setup file shown in Figs. 10 to 13.

The layout setup items will be briefly explained below. Examples of items to be set are as follows.

(1) Print method: One of one-sided/two-sided/bookbinding is designated. The one- and two-sided print processes are well known. The bookbinding print process is a method of printing data to obtain the format of a book by only folding printed sheets once and binding them. When the bookbinding print mode is designated, one of a method of folding a set of copies once, and a method of designating a predetermined number of sheets, folding each predetermined number of sheets once, and then stacking and binding them can be designated. Such twofold unit is called a bookbinding unit.

In the bookbinding print process, since a stack of a designated number of sheets, e.g., two output sheets are bound by being folded once, data cannot be

printed in the order of logical pages created by the application. The output order of logical pages, i.e., the layout order of logical pages on physical pages, is determined in advance so that logical pages are

5 allocated in turn by turning pages of the bound sheets from the right to left (this direction is designated separately). Also, the order of logical pages differs depending on whether sheets are exhausted facing up or down.

10 Since the bookbinding print process corresponds to a two-sided 2-up print process in consideration of only the format regardless of the order of pages, four logical pages are printed on the obverse and reverse surfaces of a single sheet. Hence, the required number  
15 S of sheets is given by  $S = \frac{\text{the number of logical pages}}{4}$  (with raising decimals to the next whole number). For example, when the exhaust method is face-up, and the bookbinding unit is S sheets, the  $(4 \times (P - 1) + 2 \times Q - 1)$ -th logical page and  $(4 \times (P - 1) + 4 \times S - 2 \times (Q - 1))$ -th logical page are laid out on  
20 the obverse surface (the surface printed first) of the Q-th sheet of the P-th bookbinding unit, and the  $(4 \times (P - 1) + 2 \times Q)$ -th logical page and  $(4 \times (P - 1) + 4 \times S - 2 \times Q - 1)$ -th logical pages are laid out on the  
25 reverse surface thereof. In case of the face-down

exhaust method, the reverse surface can replace the obverse surface.

(2) Book Opening Direction: This item indicates a direction to turn pages, and one of top open, right open, and left open can be designated.

(3) Bookbinding Unit: As described above, this item indicates a twofold unit in the bookbinding print process.

(4) Page Layout: One of a layout, so-called N-up print, that lays out N logical pages on one surface of a sheet (one physical page), and a layout, so-called poster print, that prints one logical page while dividing it onto a plurality of sheets can be designated.

(5) Finishing: This item can designate a process after the print process. For example, an external apparatus called an inserter can insert a sheet supplied independently of printed sheets as a cover page.

(6) Paper Source Switching: This item designates the way sheets are fed. For example, when middle insert is designated, sheets fed from one of feed ports undergo a print process, and sheets fed from the other feed port are inserted and exhausted between neighboring printed sheets. That is, sheets are alternately fed from the two feed ports.

The items that can be designated as layout setups have been explained.

In step S2202, the logical page information is acquired. The logical page is a page in data created  
5 by the application program or the like. When the Nup print process is designated, a plurality of logical pages are printed on one physical page, i.e., on one surface of one sheet. This logical page information is as shown in Fig. 14.

10 In step S2203, a page template is rendered on the basis of the information acquired in steps S2201 and S2202. The page template is a framework of each physical page in accordance with the designated layout, and is rendered in correspondence with the designated  
15 paper size and layout setups such as designation of one-sided/two-sided/bookbinding, portrait/landscape, and the like. However, when the poster print process is designated, since the combined state of images is displayed as a preview image, the above process is not  
20 applied.

In step S2204, a page number given to each page to be displayed as a preview image is rendered. In this case, pages are given in the order of logical or physical pages in accordance with the layout. In this  
25 way, the user can confirm accurate page numbers corresponding to the layout on the print preview window.

In step S2205, logical pages are rendered in correspondence with each page template. In this case, the job output setup file shown in Figs. 10 to 14 is looked up, and logical pages are rendered on a single  
5 physical page in accordance with the setups registered in the job output setup file. Intermediate data of the logical pages to be rendered are acquired with reference to the logical page information shown in Fig. 14.

10 Finally, in step S2206, the total number of pages or the required number of sheets is rendered. The total number of pages amounts to the number of logical pages, and the required number of sheets is the number of paper sheets to be output.

15 (Page Template Rendering)

Fig. 23 is a flow chart showing details of step S2203 in Fig. 22. The layout setups are acquired in step S2301 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22),  
20 and the print method is checked in steps S2302 and S2303. If the bookbinding print process is selected, a page template for bookbinding print is acquired in step S2304; if the two-sided print process is selected, a page template for two-sided print is acquired in step  
25 S2309.

If the one-sided print process is selected, it is checked in step S2306 if the middle insert print process is selected. The middle insert print process is a print method for inserting and exhausting  
5 independently fed paper sheets between neighboring output printed sheets, and is used when transparent documents for an overhead projector are printed. If the middle insert print process is selected, a page template for middle insert print is acquired in step  
10 S2207; otherwise, a page template for one-sided print is acquired in step S2308.

Lastly, in step S2305 the page template is rendered in accordance with the acquired page template data.

15 (Page Number Rendering)

Fig. 24 is a flow chart showing details of step S2204 in Fig. 22. The layout setups are acquired in step S2401 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22),  
20 and the print method is checked in steps S2402 and S2403. If the bookbinding print process is selected, page numbers for bookbinding print are rendered in step S2404; if the two-sided print process is selected, page numbers for two-sided print are printed in step S2406.  
25 On the other hand, if the one-sided print process is



selected, page numbers for one-sided print are rendered in step S2405.

(Logical Page Rendering)

Fig. 25 is a flow chart showing details of step S2205 in Fig. 22. The layout setups are acquired in step S2501 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22), and the print method is checked in steps S2502 and S2503. If the bookbinding print process is selected, logical pages for bookbinding print are rendered in step S2504; if the two-sided print process is selected, logical pages for two-sided print are printed in step S2506. On the other hand, if the one-sided print process is selected, logical pages for one-sided print are rendered in step S2505. Since logical pages are rendered in accordance with the job output setup file and logical page information, a process that does not classify according to the print method may be done.

<Details of Page Template Rendering>

Fig. 27 is a flow chart showing details of the page template rendering process in step S2305 in Fig. 23. In step S2305, the process for rendering the acquired page template is executed.

In step S2701, the vertical dimensions of individual physical pages in the job are compared to search for a page with the largest vertical size. In

this case, the job searched is a print job to be edited when the user instructs to edit the stored job or is all print jobs to be combined when the user instructs to combine job. This search is made by looking up  
5 physical page information from the output job setup file in Fig. 10 and comparing their vertical sizes. Note that data to be compared are physical pages which reflect the actual output sheet sizes and are rendered as page templates.

10           If a page with the maximum vertical size is found from all jobs to be compared, the templates of the individual pages to be displayed as preview images, which are acquired in steps S2307 to S2309 in Fig. 23 are rendered in a reduced scale, so that the template  
15 of the page with the maximum vertical size found in step S2702 falls within the display frame of the preview display. Note that the templates of the individual pages are reduced at the same ratio to maintain the relative size relationship and the  
20 vertical and horizontal directions. For example, when the job of interest includes a page with an A4 portrait size and a page with an A3 portrait size, the page template of the page with the A3 portrait size is reduced to fall within the preview display frame in the  
25 vertical direction. On the other hand, the page with the A4 portrait size is reduced at the same reduction

ratio as the A3 size so that the size relationship is maintained, i.e., the length and width of the page with the A4 portrait size respectively become 1/2 those of the page with the A3 portrait size.

5           In this manner, since all pages fall within the preview window, the preview display window need not be scrolled, thus implementing display which is very easy to see. In addition, the relative size relationship can be expressed on the preview display. Since size  
10 reduction is made to make the maximum page fall within the frame, the respective pages can be prevented from being excessively reduced, thus allowing display which is easy to see.

          Furthermore, every time a job list is edited or a  
15 page is deleted from the preview window, the edit/combine process shown in Fig. 21 is re-executed, and the preview display process in Fig. 22 is re-executed accordingly. Hence, since the process in Fig. 27 is re-executed every time the aforementioned  
20 processes are re-executed, preview display is made to always display a page with the maximum vertical size in the largest scale.

          Fig. 28 shows an example of preview display. Since "edit" of a job 2801 is designated, four pages  
25 included in the print job 2801 are displayed on a preview display window 2802. The pages displayed are

four physical pages respectively having a letter size, A4 landscape size, a 11 x 17 size, and a B4 landscape size. Upon making this display, the template sizes are reduced or enlarged in the sequence shown in Fig. 27.

5 An explanation will be given along Fig. 27. That is, as a result of comparison of the vertical dimensions of all pages, the page having the 11 x 17 size has the maximum vertical size. Hence, the template of the 11 x 17 size is zoomed to just fall within the display  
10 window 2802, and the remaining templates of the letter size, A4 size, and B4 size are zoomed to have the same ratio of sizes relative to the page of the 11 x 17 size as that of actual paper sheets. After that, these templates are rendered and displayed.

15 When the user points to a page displayed as a preview image using a pointer or the like, the size of the pointed page is displayed. In Fig. 28, the fourth page at the right end is pointed, and "B4" is displayed as its size.

20 When the user selects the third page as that having the maximum size from the state in Fig. 28 and presses a "DELETE" button 2804 in Fig. 28 to instruct "delete", the third page is deleted, and the preview window is updated, thus deleting the third page from  
25 the preview window. Fig. 29 shows this state. When the first, second, and fourth pages are searched for a

page with the maximum vertical dimension after the third page is deleted, the first page with the letter size has the maximum vertical dimension. Hence, the templates are zoomed so that the page with the letter  
5 size falls within the preview display window, and other pages are zoomed at the same ratio as the page with the letter size in the sequence shown in Fig. 27. As a result, the page with the letter size is displayed to just fall within the display window, as shown in  
10 Fig. 29.

As described above, upon displaying a preview image of a document including pages (paper sheets) of various sizes and directions, since page templates are zoomed so that a page with the maximum vertical size  
15 just falls within the preview window, the display space can be efficiently used. Also, since pages are juxtaposed and displayed, all pages can be previewed by only horizontally scrolling the window. Also, since other pages are zoomed at the same ratio as the maximum  
20 page, relative page sizes can be visually recognized on the preview display window. Also, by displaying the size of the designated page, the user can recognize not only relative sizes but also the actual size.

Note that the present invention may be applied to  
25 either a system constituted by a plurality of devices (e.g., a host computer, an interface device, a reader,

a printer, and the like), or an apparatus consisting of a single equipment (e.g., a copying machine, a facsimile apparatus, or the like).

The objects of the present invention are also  
5 achieved by supplying a storage medium, which records a program code that can implement the functions of the above-mentioned embodiments, i.e., the sequences shown in Figs. 19 to 25 and Fig. 27 to the system or apparatus, and reading out and executing the program  
10 code stored in the storage medium by a computer (or a CPU or MPU) of the system or apparatus.

In this case, the program code itself read out from the storage medium implements the functions of the above-mentioned embodiments, and the storage medium  
15 which stores the program code constitutes the present invention.

As the storage medium for supplying the program code, for example, a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape,  
20 nonvolatile memory card, ROM, and the like may be used.

The functions of the above-mentioned embodiments may be implemented not only by executing the readout program code by the computer but also by some or all of actual processing operations executed by an OS  
25 (operating system) running on the computer on the basis of an instruction of the program code.

Furthermore, the functions of the above-mentioned  
embodiments may be implemented by some or all of actual  
processing operations executed by a CPU or the like  
arranged in a function extension board or a function  
5 extension unit, which is inserted in or connected to  
the computer, after the program code read out from the  
storage medium is written in a memory of the extension  
board or unit.

As described above, print preview display that  
10 reflects the layout to be printed as faithfully as  
possible and is most easy to see without requiring the  
user to designate the layout for preview display can be  
made.

When a preview image of a document including  
15 pages with various sizes and directions is to be  
displayed, these pages are displayed as preview images  
so that a page with the maximum vertical size just  
falls within the preview display window, thus  
efficiently using the display space. Hence, all pages  
20 can be previewed by horizontally scrolling the display  
window. Also, since all the pages are zoomed at the  
same ratio as that of the maximum page, relative page  
sizes can be visually recognized on the preview display  
window. By displaying the size of the designated page,  
25 the user can recognize not only relative sizes but also  
the actual size.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the 5 specific embodiments thereof except as defined in the appended claims.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
2229  
2230  
2231  
2232  
2233  
2234  
2235  
22